

D64 / DD64 DOUBLE-HANDLE MASTER SWITCH



The double-handle D64 is a rugged switching device according IEC/EN 60947-5-1 for hoisting applications. The modular design enables the switching device to be used universally. The D64 is resistant to oil, maritime climate, ozone and UV radiation.

Mechanical life	10 million / D64 20 million / DD64 (operating cycles)
Permissible ambient temperature	Operation -40° C to +60° C
	Storage -50° C to +80° C

Contact complement 2A 250V AC 15 or 1A 24V DC 13 (standard) or 4A 250V AC 15 (special)

Available with up to 6 detented steps in each direction 6 - 0 - 6

Electronic voltage output 0,5-2,5-4,5 Volt (+5 mA) output characteristic linear power supply 4,6-5,5 Volt DC

Electronic output 0 - +/-10 Volt or 4-20 mA output characteristic linear power supply 12-30 Volt DC

Electronic PWM output 0 - 2000mA output characteristic linear power supply 12-30 Volt DC

Wire-wound potentiometer with centre tap linear resistance 2 x 0.5K, 2 x 1K, 2 x 2K, 2 x 5K, 2 x 10K

SENETT CONTROLS
 **GESSMANN** GROUP
Industrial Controllers

225 Admiral Blvd. Mississauga, On., L5T 2T3
Tel: 905.564.0167 Email: sales@senett.ca
Fax: 905.564.6633 Website: www.senett.ca