

# KST19 CONTROL STATION



Permissible ambient temperature  
Operation -40° C to +60° C  
Storage -50° C to +80° C  
Degree of protection front  
IP 54 IEC / EN 6052

The swivelling crane control unit KST 19 is designed in accordance with ergonomical and medical guidelines and provides a high grade of comfort.

The standard design includes following:

**Equipment boxes:** Plastic with armrest. The top panel of the equipment box (screwed together) includes the devices. Wiring is done through a conduit into the cross-member. (Terminal block).

**Seat:** Comfortable spring mounted seat KFS 10, with a pneumatic vibration absorption system by compressor 24 VDC, weight adjustment and airpermeable artificial leather or textil material, with headrest and seat cushion deep prolongation.

**Manual adjustments:** 1 Crane control unit swiveling; 2 Horizontal adjustment seat with equipment boxes; 3 Vertical weight adjustment seat incl. equipment boxes; 5 Backrest adjustable; 6 Horizontal adjustment of seat; 7 Left / right equipment box is tiltable; 8 Horizontal adjustment equipment box; 9 Height adjustment equipment boxes to seat; 10 Equipment boxes adjustment; 11 Inclination adjustment of equipment boxes; 12 Monitor mounting support rotatable

**Cross-member:** Steel section, can be opened (system tray) for easy accessibility of the terminals.

**Swivel base:** Zero-end-float spring-loaded bearing. Rotational movement 180° right, 90° left, stopped by friction brake.

**Surface treatment:** Anti-corrosion primer, top coat: 2 coats of epoxy-resin paint, standard colour RAL 7000 fairy-grey, textured varnish. All non-painted metal parts are electrogalvanized and chromed.

**SENETT CONTROLS**  
 **GESSMANN** GROUP  
Industrial Controllers

225 Admiral Blvd. Mississauga, On., L5T 2T3  
Tel: 905.564.0167 Email: sales@senett.ca  
Fax: 905.564.6633 Website: www.senett.ca