

LCS5R-CC CONTROL STATION



Permissible ambient temperature
Operation -40° C to +60° C
Storage -50° C to +80° C
Degree of protection front
IP 54 IEC / EN 60529

The swivelling crane control unit LCS5R-CC is ergonomically designed and provides a high degree of comfort. The standard design includes following:

Custom angled control boxes to reduce turning radius

Equipment boxes: Sheet steel. The top lid with the devices can be raised for easy access to the terminal strip.

Seat: Comfortable spring mounted seat CCS-G1 with a hydraulic shock absorber, weight adjustment. Air permeable artificial leather or textil material, with headrest and armrests.

Adjusting possibilities: Seat horizontally and vertically. Inclination of cushion, backrest and armrest also adjustable. Weight setting for optimum spring suspension.

Cross-member: Sheet steel, top of which can be raised to lay cabling. The seat can be tilted forward so that the cable duct in the cross-member is accessible.

Swivel base: Zero-end-float spring-loaded bearing. Rotational movement 180° right, 90° left, stopped by friction brake.

Surface treatment: Anti-corrosion primer, top coat: 2 coats of epoxy-resin paint, standard colour RAL 7032 pebble-grey, textured varnish. All non-painted metal parts are electrogalvanized and chromed.

SENETT CONTROLS
 **GESSMANN**® GROUP
Industrial Controllers

225 Admiral Blvd. Mississauga, On., L5T 2T3
Tel: 905.564.0167 Email: sales@senett.ca
Fax: 905.564.6633 Website: www.senett.ca