

# N6 ROTARY SWITCH



The rotary switch N6 is a rugged switching device according IEC/EN 60947-5-1 for hoisting and electro-hydraulic applications. The modular design enables the switching device to be used universally. The N6 is resistant to oil, maritime climate, ozone and UV radiation.

Mechanical life	10 million (operating cycles)
Permissible ambient temperature	Operation -40° C to +60° C
	Storage -50° C to +80° C

Contact complement 2A 250V AC 15 or 1A 24V DC 13 (standard) or 4A 250V AC 15 (special)  
Electronic voltage output 0,5-2,5-4,5 Volt (+5 mA) output characteristic linear power supply 4,6-5,5 Volt DC  
Electronic output 0 - +/-10 Volt or 4-20 mA output characteristic linear power supply 12-30 Volt DC  
Electronic PWM output 0 - 2000mA output characteristic linear power supply 12-30 Volt DC  
Potentiometer with or without centre tap linear resistance 2 x 0.5k, 2 x 1k, 2 x 2k, 2 x 5k, 2 x 10k

**SENETT CONTROLS**  
 **GESSMANN** GROUP  
Industrial Controllers

225 Admiral Blvd. Mississauga, On., L5T 2T3  
Tel: 905.564.0167 Email: [sales@senett.ca](mailto:sales@senett.ca)  
Fax: 905.564.6633 Website: [www.senett.ca](http://www.senett.ca)