

S21 / SS21 SINGLE AXIS MASTER SWITCH



The single-axis controller S21 is a rugged switching device according IEC/EN 60947-5-1 for electro-hydraulic applications. The modular design enables the switching device to be used universally. The S21 is resistant to oil, maritime climate, ozone and UV radiation.

Mechanical life	6 million / S21 10 million / SS21 (operating cycles)
Permissible ambient temperature	Operation -40° C to +60° C
	Storage -50° C to +80° C

Contact complement 2 A 250 V AC 15 or 3 A 24 V DC 13

Electronic output 0.5-2.5-4.5 Volt (+5mA) output characteristic linear power supply 4,6-5,5 Volt DC

Electronic output 0 - +/-10 Volt or 4-20 mA output characteristic linear power supply 12-30 Volt DC

Electronic PWM output 0 - 2000mA output characteristic linear power supply 12-30 Volt DC

Potentiometer with or without centre tap linear resistance 2 x 0.5k, 2 x 1k, 2 x 2k, 2 x 5k, 2 x 10k

SENETT CONTROLS
 **GESSMANN** GROUP
Industrial Controllers

225 Admiral Blvd. Mississauga, On., L5T 2T3
Tel: 905.564.0167 Email: sales@senett.ca
Fax: 905.564.6633 Website: www.senett.ca