

S23 SINGLE AXIS MASTER SWITCH



The single-axis controller S23 is a rugged switching device according IEC/EN 60947-5-1 for remote control and other applications.

The S23 is resistant to oil, maritime climate, ozone and UV radiation.

Mechanical life

6 million (operating cycles)

Permissible ambient temperature

Operation -40° C to +60° C

Storage -50° C to +80° C

Degree of protection front:

IP 65 IEC / IEN 60529

Contact complement 2 A 250 V AC 15 or 3 A 24 V DC 13

Electronic output 0.5-2.5-4.5 Volt (+5mA) output characteristic linear power supply 4,6-5,5 Volt DC

Electronic output 0 - +/-10 Volt or 4-20 mA output characteristic linear power supply 12-30 Volt DC

Electronic PWM output 0 - 2000mA output characteristic linear power supply 12-30 Volt DC

Potentiometer with or without centre tap linear resistance 2 x 0.5k, 2 x 1k, 2 x 2k, 2 x 5k, 2 x 10k

SENETT CONTROLS
 **GESSMANN** GROUP
Industrial Controllers

225 Admiral Blvd. Mississauga, On., L5T 2T3

Tel: 905.564.0167 Email: sales@senett.ca

Fax: 905.564.6633 Website: www.senett.ca