

V8 / VV8 MULTI-AXIS MASTER SWITCH



The multi-axis controller V8 is a rugged switching device according IEC/EN 60947-5-1 for electro-hydraulic applications. The modular design enables the switching device to be used universally. The V8 is resistant to oil, maritime climate, ozone and UV radiation.

Mechanical life	10 million / V8 20 million / VV8 (operating cycles)
Permissible ambient temperature	Operation -40° C to +60° C
	Storage -50° C to +80° C

Contact complement 0.5A 110V AC 15 or 1.5A 24V DC 13

I min > 0.2 mA 2V DC 12 Gold plated for max. load of 0.12 Watt (standard)

Electronic voltage output 0,5-2,5-4,5 Volt (+5 mA) output characteristic linear power supply 4,6-5,5 Volt DC

Electronic output 0 - +/-10 Volt or 4-20 mA output characteristic linear power supply 12-30 Volt DC

Electronic PWM output 0 - 2000mA output characteristic linear power supply 12-30 Volt DC

Profi-Bus, CAN-Bus interface

SENETT CONTROLS
 **GESSMANN** GROUP
Industrial Controllers

225 Admiral Blvd. Mississauga, On., L5T 2T3
Tel: 905.564.0167 Email: sales@senett.ca
Fax: 905.564.6633 Website: www.senett.ca